



TotalEnergies

SAFETY DATA SHEET

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by
Commission Regulation (EU) 2020/878

DYNATRANS VX FE

SDS #: 080084

previous revision date : 2023/06/30

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : DYNATRANS VX FE
UFI : GYAX-689P-V001-KWYX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses
Manual Transmission Fluid Formulation additives, lubricants and greases - Industrial General use of lubricants and greases in vehicles or machinery - Industrial General use of lubricants and greases in vehicles or machinery - Professional

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing Croatia d.o.o.,
Horvatova 80a, 10000 Zagreb, Hrvatska.
Tel: + 385 1 6700 339
ms.logistika@totalenergies.com

Contact

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Center

Telephone number : Telephone number for medical information in case of poisoning: +385 (0) 1
23-48-342

Emergency phone: 112

Supplier

Telephone number : Total Emergency phone: +44 1235 239670



SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Sens. 1B, H317

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

For more details about adverse physical, human health and environmental effects, see sections 9 to 12.

2.2 Label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 - May cause an allergic skin reaction.

Precautionary statements

Prevention : P261 - Avoid breathing gas, vapor or spray.
P280 - Wear protective gloves.

Response : P362 + P364 - Take off contaminated clothing and wash it before reuse.
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 - If skin irritation or rash occurs: Get medical advice or attention.

Storage : Not applicable.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

Contains : Benzenesulfonic acid, propenated, calcium salt, overbased

Supplemental label elements : Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles : Not applicable.

2.3 Other hazards

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification : Hazard of slipping on spilled product.

**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

Product/substance	Identifiers	% (w/w)	Classification	Specific Conc. Limits, M-factors and ATEs	Type
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥25 - ≤50	Asp. Tox. 1, H304	-	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	-	[1]
Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9 Index: 649-469-00-9	≤3	Asp. Tox. 1, H304	-	[1]
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	REACH #: 01-2119493635-27 EC: 224-235-5 CAS: 4259-15-8	<2.5	Eye Dam. 1, H318 Aquatic Chronic 2, H411	Eye Dam. 1, H318: C ≥ 50%	[1]
Benzenesulfonic acid, propenated, calcium salt, overbased	REACH #: 01-2119657986-16 EC: 271-877-7 CAS: 68610-84-4	≤3	Skin Sens. 1B, H317 Aquatic Chronic 4, H413 See Section 16 for the full text of the H statements declared above.	-	[1]

Additional information : Mineral oil of petroleum origin. Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures**4.1 Description of first aid measures**

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.



- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** :
irritation
redness
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.



Hazardous combustion products : carbon monoxide
carbon dioxide
Silicon Dioxide
phosphorus oxides
sulfur oxides
Hydrogen sulfide
Mercaptans
Zinc oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and materials for containment and cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product.

6.4 Reference to other sections : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.



SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

- Recommendations** : See exposure scenarios
- Industrial sector specific solutions** : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.

- Recommended monitoring procedures** : Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

- Advisory OEL** : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs



Product/substance	Type	Exposure	Value	Population	Effects
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), solvent-dewaxed heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), solvent-dewaxed light paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	DNEL	Long term Oral	0.19 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	1.67 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	4.8 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	6.6 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	9.6 mg/kg bw/day	Workers	Systemic
Benzenesulfonic acid, propenated, calcium salt, overbased	DNEL	Short term Oral	50 mg/kg bw/day	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Name	Method Detail
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
zinc bis[O,O-bis(2-ethylhexyl)] bis (dithiophosphate)	Fresh water	0.004 mg/l	-
	Marine water	0.0046 mg/l	-
	Fresh water sediment	322 µg/kg dwt	-
	Marine water sediment	32.2 µg/kg dwt	-
	Soil	61.9 µg/kg dwt	-
	Sewage Treatment Plant	3.8 mg/l	-
	Secondary Poisoning	8.33 mg/kg	-



Benzenesulfonic acid, propenated, calcium salt, overbased	Fresh water	1 mg/l	-
	Marine water	1 mg/l	-
	Fresh water sediment	43500 mg/kg dwt	-
	Marine water sediment	3480 mg/kg dwt	-
	Soil	8850 mg/kg dwt	-
	Sewage Treatment Plant	1000 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : safety glasses with side-shields, EN 166.

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Hydrocarbon-proof gloves

nitrile rubber

Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency

Body protection : Wear work clothing with long sleeves.

Non-skid safety shoes or boots

Respiratory protection : Ensure adequate ventilation and check that a safe, breathable atmosphere is present before entry into confined spaces. In case of inadequate ventilation wear respiratory protection: Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**SECTION 9: Physical and chemical properties**

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical properties**Appearance**

Physical state	: Liquid.
Color	: Amber.
Odor	: Characteristic.
pH	: Not applicable. Product is non-soluble (in water).
Melting point/freezing point	: Technically not possible to measure
Initial boiling point and boiling range	: >316°C [EN ISO 3405]
Flash point	: Open cup: 254°C [ISO 2592]
Flammability	: Not applicable.
Lower and upper explosion limit	: Lower: 0.9% Upper: 7%
Vapor pressure	: <0.013 kPa [room temperature] [ASTM D 5191] Not applicable. [50°C]
Vapor density	: >2 [Air = 1]
Relative density	: 0.855 [ISO 12185]
Density	: 0.855 g/cm ³ [15°C] [ISO 12185]
Solubility(ies)	:

Media	Result
water	Not soluble

Miscible with water	: No.
Partition coefficient: n-octanol/water	: Not applicable.
Auto-ignition temperature	: >250°C [ASTM E 659]
Decomposition temperature	: Not applicable.
Viscosity	: Dynamic (room temperature): Not available. Kinematic (room temperature): Not available. Kinematic (40°C): 40.3 mm ² /s [ISO 3104]

Particle characteristics

Median particle size	: Not applicable.
----------------------	-------------------

9.2 Other information

Pour point	: -42°C (-43.6°F)
------------	-------------------

SECTION 10: Stability and reactivity

10.1 Reactivity : No specific test data related to reactivity available for this product or its ingredients.

10.2 Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.



10.4 Conditions to avoid : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible materials : Strong oxidizing agents

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	Read across OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	Read across OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Distillates (petroleum), solvent-dewaxed light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	LD50 Dermal	Rabbit - Male	>5 g/kg	-	OECD 402
	LD50 Oral	Rat - Male	3.1 g/kg	-	OECD 401
	LD50 Dermal	Rat	5.1 mg/l	4 hours	-
Benzenesulfonic acid, propenated, calcium salt, overbased	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	4001 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 423

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapors) (mg/l)	Inhalation (dusts and mists) (mg/l)
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	3100	N/A	N/A	N/A	N/A
Benzenesulfonic acid, propenated, calcium salt, overbased	N/A	4001	N/A	N/A	5.1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion



Product/substance	Result	Species	Score	Exposure	Test
zinc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate)	Eyes - Cornea opacity	Rabbit	1.17	-	OECD 405
	Skin - Edema	Rabbit	0.22	4 hours	OECD 404

Conclusion/Summary

- Skin** : Based on available data, the classification criteria are not met.
- Eyes** : Based on available data, the classification criteria are not met. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required.
- Respiratory** : Based on available data, the classification criteria are not met.

Sensitization

Product/substance	Route of exposure	Species	Result
zinc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate)	skin	Guinea pig	Not sensitizing

Conclusion/Summary

- Skin** : Based on available data, the classification criteria are met.
- Respiratory** : Based on available data, the classification criteria are not met.

Mutagenicity

Product/substance	Test	Experiment	Result
zinc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate)	OECD 471	Experiment: In vitro Subject: Bacteria	Negative
	OECD 474	Experiment: In vivo Subject: Mammalian-Animal	Negative

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Carcinogenicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Reproductive toxicity

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Teratogenicity

Product/substance	Result	Species	Dose	Exposure
zinc bis[O,O-bis (2-ethylhexyl)] bis (dithiophosphate)	Negative - Oral	Rat - Male, Female	30 mg/kg NOAEL	-

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

- Conclusion/Summary** : Based on available data, the classification criteria are not met.

Aspiration hazard



Product/substance	Result
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation. May cause an allergic skin reaction.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact :
 irritation
 redness
 dryness
 cracking
Ingestion : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

Product/substance	Result	Species	Dose	Exposure
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	Sub-acute NOAEL Oral	Rat - Male, Female	125 mg/kg	-

Conclusion/Summary : Not available.
General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
Carcinogenicity : No known significant effects or critical hazards.
Mutagenicity : No known significant effects or critical hazards.
Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties



This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/substance	Result	Species	Exposure	Test
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	-
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours	OECD 203
Distillates (petroleum), solvent-dewaxed light paraffinic	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute EL50 ≥100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
	Acute EC50 240 mg/l Fresh water	Algae - <i>Desmodesmus subspicatus</i>	72 hours	OECD 201
	Acute EL50 75 mg/l Fresh water	<i>Daphnia</i>	48 hours	OECD 202
Benzenesulfonic acid, propenated, calcium salt, overbased	Acute LC50 46 mg/l Fresh water	Fish - <i>Cyprinodon variegatus</i>	96 hours	OECD 203
	Acute LL50 4.4 mg/l Fresh water	Fish - <i>Oncorhynchus mykiss</i>	96 hours	OECD 203
	Chronic NOEC 0.4 mg/l Fresh water	<i>Daphnia</i>	21 days	OECD 211
	Acute EC50 >1000 mg/l	<i>Daphnia</i> - <i>Daphnia magna</i>	48 hours	-
	Acute LC50 1000 mg/l	Algae - <i>Pseudokirchnerella subcapitata</i>	72 hours	-
	Acute NOEL 1.8 mg/l	<i>Daphnia</i> - <i>Daphnia magna</i>	48 hours	OECD 202



Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed light paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	-	<5 % - 28 days	-	-

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed heavy paraffinic	-	-	Not readily
Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	Not readily
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	-	-	Not readily
Benzenesulfonic acid, propenated, calcium salt, overbased	-	-	Not readily

12.3 Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low
Distillates (petroleum), solvent-dewaxed light paraffinic	3.1	-	Low
zinc bis[O,O-bis(2-ethylhexyl)] bis(dithiophosphate)	3.59	-	Low
Benzenesulfonic acid, propenated, calcium salt, overbased	5.8	64	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.



Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration >= 0,1 %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05*

Packaging

Methods of disposal : The generation of waste should be avoided or minimized wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-



14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorization

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

Labeling : Not applicable.

Other EU regulations

Take note of Dir 94/33/EC on the protection of young people at work. Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Air

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

Industrial emissions (integrated pollution prevention and control) - Water

Explosive precursors : Not applicable.

Ozone depleting substances (1005/2009/EU)

Not listed.

Prior Informed Consent (PIC) (649/2012/EU)

Not listed.

Persistent Organic Pollutants

Not listed.

Seveso Directive

This product is not controlled under the Seveso Directive.

National regulations

National regulatory information



The Chemical act
Ordinance on limit values on hazard substances exposure during work and biological threshold values
E.g Law on hazard chemical transport
Law on health and safety
Act on Sustainable Waste Management NN no. 94/13
OG no. 73/17
Ordinance on Waste Management NN. 23/14
Official Gazette no. 15/14
OG no. 121/15
OG no. 132/15
Ordinance on packaging and packaging waste NN no. 88/15
78/16
Ordinance on the waste catalogue NN no. 90/15

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

LU - Luxembourg prohibited chemicals in the workplace

Not listed.

Inventory list

Australia inventory (AIIIC)	: All components are listed or exempted.
Canada inventory (DSL/NDSL)	: All components are listed or exempted.
China inventory (IECSC)	: At least one component is not listed.
Europe inventory (EC)	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.



Vietnam inventory : Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical Safety Assessment : See exposure scenarios

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms : ACGIH = American Conference of Governmental Industrial Hygienists
 ATE = Acute Toxicity Estimate
 BCF = Bioconcentration Factor
 CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
 DNEL = Derived No Effect Level
 DMEL = Derived Minimal Effect Level
 DMSO = Dimethyl Sulfoxide
 EL50 = median Effective Loading
 EUH statement = CLP-specific Hazard statement
 HSE = Health, Safety and Environment
 IC50 = Half maximal inhibitory concentration
 IDHL = Immediately dangerous to life or health
 LC50 = Median lethal concentration
 LD50 = Median lethal dose
 LL50 = median Lethal Loading
 LogKow = logarithm of the octanol/water partition coefficient
 N/A = Not available
 NIOSH = National Institute of Occupational Safety and Health
 NOAEL = No Observed Adverse Effect Level
 NOEC No Observed Effect Concentration
 NOEL = No Observed Effect Level
 NOELR = No observed Effect Loading Rate
 OECD = Organisation for Economic Co-operation and Development
 OEL = Occupational Exposure Limit
 PBT = Persistent, Bioaccumulative and Toxic
 PNEC = Predicted No Effect Concentration
 QSAR = Quantitative Structure–Activity Relationship
 REL = Recommended Exposure Limit
 STEL = Short Term Exposure Limit
 TLV = Threshold Limit Value
 TWA = Time Weight Average
 VOC = Volatile Organic Compound
 vPvB = Very Persistent and Very Bioaccumulative
 Unique Formula Identifier (UFI)
 UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Sens. 1B, H317	Calculation method

Full text of abbreviated H statements



H304 H317 H318 H411 H413	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects. May cause long lasting harmful effects to aquatic life.
--------------------------------------	--

Full text of classifications [CLP/GHS]

Aquatic Chronic 2 Aquatic Chronic 4 Asp. Tox. 1 Eye Dam. 1 Skin Sens. 1B	AQUATIC HAZARD (LONG-TERM) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 4 ASPIRATION HAZARD - Category 1 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 SKIN SENSITIZATION - Category 1B
--	---

Date of revision : 2024/07/29

previous revision date : 2023/06/30

Version : 4

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 080084
Product name : DYNATRANS VX FE

Section 1 - Title

Short title of the exposure scenario : Formulation additives, lubricants and greases - Industrial

List of use descriptors : **Identified use name:** Formulation additives, lubricants and greases - Industrial
Process Category: PROC01, PROC02, PROC03, PROC04, PROC05, PROC08a, PROC08b, PROC09, PROC15
Sector of end use: SU03, SU10
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC02

Health Contributing scenarios : **General measures applicable to all activities**
General exposures Use in contained systems Elevated temperature - PROC02
Mixing operations Closed systems Batch processes at elevated temperatures - PROC03
Mixing operations Open systems Batch processes at elevated temperatures - PROC04, PROC05
Mixing operations (open systems) - PROC04, PROC05
Process sampling - PROC04, PROC08b
Bulk transfers Dedicated facility - PROC08b
Drum/batch transfers Dedicated facility - PROC08b
Drum/batch transfers Non-dedicated facility - PROC08a
Equipment cleaning and maintenance - PROC08a, PROC08b
Drum and small package filling - PROC09
Laboratory activities - PROC15
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario	: Industrial formulation of lubricant additives, lubricants and greases. Includes material transfers, mixing, large and small scale packing, sampling, maintenance.
---	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

No exposure scenario required

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article	: Covers percentage substance in the product up to 100 %. (unless stated differently)
Physical state	: Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure
Amounts used	: Not applicable.
Frequency and duration of use/exposure	: Covers daily exposures up to 8 hours (unless stated differently)
Human factors not influenced by risk management	: Not applicable.
Other operational conditions affecting worker exposure	: Covers percentage substance in the product up to 100% (unless stated differently)

Conditions and measures related to personal protection, hygiene and health evaluation

Date of issue/Date of revision : 3/11/2020

20/31

Advice on general occupational hygiene : Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.

Personal protection : Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: General exposures Use in contained systems Elevated temperature

No other specific measures identified.

Contributing scenario controlling worker exposure for 4: Mixing operations Closed systems Batch processes at elevated temperatures

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 5: Mixing operations Open systems Batch processes at elevated temperatures

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours.

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 6: Mixing operations (open systems)

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 7: Process sampling

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 1 hour per day.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 8: Bulk transfers Dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 9: Drum/batch transfers Dedicated facility

Ventilation control measures : Provide extract ventilation to points where emissions occur.

Contributing scenario controlling worker exposure for 10: Drum/batch transfers Non-dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 1 hour per day.

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 11: Equipment cleaning and maintenance

Technical conditions and measures to control dispersion from source towards the worker : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down and flush system prior to equipment break-in or maintenance.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Clear spills immediately.

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 12: Drum and small package filling

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 13: Laboratory activities

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours.

Contributing scenario controlling worker exposure for 14: Storage

Engineering controls : Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: General exposures Use in contained systems Elevated temperature

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 4: Mixing operations Closed systems Batch processes at elevated temperatures

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 5: Mixing operations Open systems Batch processes at elevated temperatures

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 6: Mixing operations (open systems)

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 7: Process sampling

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 8: Bulk transfers Dedicated facility

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 9: Drum/batch transfers Dedicated facility

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 10: Drum/batch transfers Non-dedicated facility

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 11: Equipment cleaning and maintenance

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 12: Drum and small package filling

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 13: Laboratory activities

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 14: Storage

Exposure assessment (human):	: The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Industrial

Identification of the substance or mixture

Product definition : Mixture
Code : 080084
Product name : DYNATRANS VX FE

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Industrial

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Industrial
Process Category: PROC01, PROC02, PROC08b, PROC09
Sector of end use: SU03
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC04, ERC07

Health Contributing scenarios : **General measures applicable to all activities**
General exposures (closed systems) - PROC01
Initial factory fill of equipment Use in contained systems - PROC02, PROC09
Initial factory fill of equipment Open systems - PROC08b
Operation of equipment containing engine oils and similar Use in contained systems - PROC01
Equipment cleaning and maintenance - PROC08b
Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature) - PROC08b
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
--	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

No exposure scenario required

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100% (unless stated differently).

Physical state : Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours (unless stated differently).

Other operational conditions affecting worker exposure : Assumes use at not more than 20°C above ambient temperature, unless stated differently. unless stated differently.
Assumes a good basic standard of occupational hygiene has been implemented.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.

Personal protection : Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: General exposures (closed systems)

No other specific measures identified.

Contributing scenario controlling worker exposure for 4: Initial factory fill of equipment Use in contained systems

No other specific measures identified.

Contributing scenario controlling worker exposure for 5: Initial factory fill of equipment Open systems

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours.

Ventilation control measures : Provide a good standard of general or controlled ventilation (10 to 15 air changes per hour)

Contributing scenario controlling worker exposure for 6: Operation of equipment containing engine oils and similar Use in contained systems

No other specific measures identified.

Contributing scenario controlling worker exposure for 7: Equipment cleaning and maintenance

Technical conditions and measures at process level (source) to prevent release : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down system prior to equipment break-in or maintenance.

Ventilation control measures : Provide a good standard of general ventilation (not less than 3 to 5 air changes per hour).

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 8: Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Technical conditions and measures to control dispersion from source towards the worker : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down system prior to equipment break-in or maintenance.

Ventilation control measures : Provide extract ventilation to emission points when contact with warm (>50°C) lubricant is likely.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with intensive management supervision controls.

Contributing scenario controlling worker exposure for 9: Storage

Engineering controls : Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: General exposures (closed systems)

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 4: Initial factory fill of equipment Use in contained systems

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 5: Initial factory fill of equipment Open systems

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 6: Operation of equipment containing engine oils and similar Use in contained systems

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 7: Equipment cleaning and maintenance

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 8: Equipment cleaning and maintenance Operation is carried out at elevated temperature (> 20°C above ambient temperature)

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 9: Storage

Exposure assessment (human): : The risk Management Mesures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.

Annex to the extended Safety Data Sheet (eSDS)

Professional

Identification of the substance or mixture

Product definition : Mixture
Code : 080084
Product name : DYNATRANS VX FE

Section 1 - Title

Short title of the exposure scenario : General use of lubricants and greases in vehicles or machinery - Professional

List of use descriptors : **Identified use name:** General use of lubricants and greases in vehicles or machinery - Professional
Process Category: PROC01, PROC02, PROC08a, PROC08b, PROC20
Sector of end use: SU22
Subsequent service life relevant for that use: No.
Environmental Release Category: ERC09a, ERC09b

Health Contributing scenarios : **General measures applicable to all activities**
Operation of equipment containing engine oils and similar Use in contained systems - PROC01
Material transfers Non-dedicated facility - PROC08a
Equipment cleaning and maintenance Dedicated facility - PROC08b, PROC20
Storage - PROC01, PROC02

Processes and activities covered by the exposure scenario	: Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.
--	---

Section 2 - Exposure controls

Contributing scenario controlling environmental exposure for 1:

No exposure scenario required

Contributing scenario controlling worker exposure for 2: General measures applicable to all activities

Concentration of substance in mixture or article : Covers percentage substance in the product up to 100% (unless stated differently).

Physical state : Liquid, vapor pressure < 0.5 kPa at Standard Temperature and Pressure.

Frequency and duration of use/exposure : Covers daily exposures up to 8 hours (unless stated differently).

Other operational conditions affecting worker exposure : Assumes use at not more than 20°C above ambient temperature, unless stated differently. unless stated differently.
Assumes a good basic standard of occupational hygiene has been implemented.

Conditions and measures related to personal protection, hygiene and health evaluation

Advice on general occupational hygiene : Avoid direct skin contact with product. Identify potential areas for indirect skin contact. Wear gloves (tested to EN 374) if hand contact with substance likely. Clean up contamination/spills as soon as they occur. Wash off any skin contamination immediately. Provide basic employee training to prevent/minimise exposures and to report any skin problems that may develop. Avoid direct eye contact with product, also via contamination on hands.

Personal protection : Use suitable eye protection.

Contributing scenario controlling worker exposure for 3: Operation of equipment containing engine oils and similar Use in contained systems

No other specific measures identified.

Contributing scenario controlling worker exposure for 4: Material transfers Non-dedicated facility

Frequency and duration of use/exposure : Avoid carrying out activities involving exposure for more than 4 hours.

Conditions and measures related to personal protection, hygiene and health evaluation

Personal protection : Wear chemically resistant gloves (tested to EN374) in combination with specific activity training.

Contributing scenario controlling worker exposure for 5: Equipment cleaning and maintenance Dedicated facility

Technical conditions and measures at process level (source) to prevent release : Retain drain-downs in sealed storage pending disposal or for subsequent recycle.

Engineering controls : Drain down system prior to equipment break-in or maintenance.

Contributing scenario controlling worker exposure for 6: Storage

Engineering controls : Store substance within a closed system.

Section 3 - Exposure estimation and reference to its source

Website: : Not applicable.

Exposure estimation and reference to its source - Environment: 1:

Exposure assessment (environment): : Used ECETOC TRA model.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 2: General measures applicable to all activities

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 3: Operation of equipment containing engine oils and similar Use in contained systems

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 4: Material transfers Non-dedicated facility

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 5: Equipment cleaning and maintenance Dedicated facility

Exposure assessment (human): : The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.

Exposure estimation and reference to its source : Not available.

Exposure estimation and reference to its source - Workers: 6: Storage

Exposure assessment (human):	: The risk Management Measures/Operational Conditions that are identified in the Exposure Scenario are the outcome of a quantitative and qualitative assessment that covers this product.
Exposure estimation and reference to its source	: Not available.

Section 4 - Guidance to DU to evaluate whether he works inside the boundaries set by the ES

Environment	: Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. Further details on scaling and control technologies are provided in SPERC factsheet. If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a site-specific chemical safety assessment is required. For further information see www.atiel.org/reach/introduction .
Health	: Where other risk management measures/operational conditions are adopted, then users should ensure that risks are managed to at least equivalent levels. For further information see www.atiel.org/reach/introduction .

Additional good practice advice beyond the REACH CSA

Environment	: Not available.
Health	: Not available.